



Meler compatible

Heated hoses



OGAN Heating Hoses developed and produced for Meler glue systems are produced from hi-tech components. OGAN Heating Hoses are highly flexible for manual hand gun and robotic applications and extra strengthened to prevent external and internal structural deformation which may occur from dynamic movements.

- 100% compliant with Meler systems,
- High quality PTFE hose have a continuous working temperature of 260 °C and a burst pressure of 4 times the working pressure,
- PTFE heavy-duty teflon internal structure is resistant to all solvents, acids and aggressive adhesives under high temperature operating conditions,
- Guarantees long lifetime when installed and used according to the instructions,
- Available with the ID 6 , 8 , 13 , 16 , 20 ,25 mm and any length between 0.4 m – 15 m.
- Available in Standard, High-Pressure and Water-Protected versions. Please refer to below tables.
- Can also be produced based on your specific requests.

Meler Compatible heated hose DN8

Internal Diameter : 8 mm / Voltage : 230 V 50/60 Hz / Sensor : PT100

Max. operating Pressure : 150 bar at 210 °C



Length	MELER P/N	OGAN P/N
0,60 m	102211010	MLR-102211010
0,80 m	102211180	MLR-102211180
1,20 m	102211050	MLR-102211050
1,80 m	102211060	MLR-102211060
2,40 m	102211070	MLR-102211070
3,00 m	102211080	MLR-102211080
3,60 m	102211090	MLR-102211090
4,20 m	102211100	MLR-102211100
4,80 m	102211110	MLR-102211110
5,40 m	102211120	MLR-102211120
6,00 m	102211130	MLR-102211130
7,20 m	102211150	MLR-102211150
8,00 m	102211060	MLR-102211160
9,00 m	102211020	MLR-102211020
10,00 m	102211030	MLR-102211030
12,00 m	102211040	MLR-102211040

Meler Compatible heated hose DN13

Internal Diameter : 13 mm / Voltage : 230 V 50/60 Hz / Sensor : Ni120

Max. operating Pressure : 110 bar at 210 °C



Length	MELER P/N	OGAN P/N
0,60 m	102311030	MLR-102311030
1,20 m	102311040	MLR-102311040
1,80 m	102311050	MLR-102311050
2,40 m	102311060	MLR-102311060
3,00 m	102311070	MLR-102311070
3,60 m	102311080	MLR-102311080
4,20 m	102311090	MLR-102311090
4,80 m	102311100	MLR-102311100
5,40 m	102311110	MLR-102311110
6,00 m	102311120	MLR-102311120
7,20 m		
8,00 m		
9,00 m		
10,00 m	102311010	MLR-102311010
12,00 m	102311020	MLR-102311020

Meler Compatible heated hose DN8

Internal Diameter : 8 mm / Voltage : 230 V 50/60 Hz / Sensor : Ni120

Max. operating Pressure : 150 bar at 210 °C



Length	MELER P/N	OGAN P/N
0,60 m	102212010	MLR-102212010
1,20 m	102212020	MLR-102212020
1,80 m	102212030	MLR-102212030
2,40 m	102212040	MLR-102212040
3,00 m	102212050	MLR-102212050
3,60 m	102212060	MLR-102212060
4,20 m	102212070	MLR-102212070
4,80 m	102212080	MLR-102212080
6,00 m	102212100	MLR-102212100
7,20 m	102212120	MLR-102212120

Headquarters

Ogan Endustriyel Isi Hortum San. Ltd. Sti.

Deri OSB 3 Nolu Giriş, Yan Sanayi Cad.

Biye Sok. No:31 Aydinli

Tuzla 34953 İstanbul, Turkey

Tel: +90 216 591 0343

+90 533 469 1009 (for English)

e-mail: info@ogan.com.tr

foreigntrade@ogan.com.tr (for English)

Web: www.ogan.com.tr

UK Distributor

Hot Melt Services Ltd.

Unit 3, Wymeswold Industrial Park,

Burton On The Wolds,

Loughborough, LE12 5TR United Kingdom.

Tel: 01509 889 511

e-mail: services@hotmeltsservices.com

Web: <https://hotmeltsservices.com>

